

ESLINGAS REDONDAS TRENZADAS



ESLINGAS REDONDAS TRENZADAS

6 PARTES

CODIGO	Capacidad de carga en vertical (kgs)	Capacidad de carga enlazada (kgs)	Capacidad de carga en "U" (kgs)
6VR1	6,700	5,300	13,400
6VR2	13,500	10,800	27,000
6VR3	21,400	17,100	42,800
6VR4	27,000	21,600	54,000
6VR5	33,600	26,800	67,200
6VR6	42,800	34,200	85,600
6VR7	54,000	43,200	108,000
6VR8	63,700	50,900	127,400
6VR9	79,000	63,200	158,000



SPEC

SOLUCIONES PROFESIONALES EN CARGAS

ESLINGAS REDONDAS TRENZADAS

8 PARTES

CODIGO	Capacidad de carga en vertical (kgs)	Capacidad de carga enlazada (kgs)	Capacidad de carga en "U" (kgs)
8VR1	9,000	7,200	18,000
8VR2	18,000	14,400	36,000
8VR3	28,500	22,800	57,000
8VR4	36,000	30,600	72,000
8VR5	44,900	35,900	89,800
8VR6	57,100	45,600	114,200
8VR7	72,000	57,600	144,000
8VR8	85,000	68,000	170,000
8VR9	105,300	84,200	210,600



SPEC
SOLUCIONES PROFESIONALES EN CARGAS