



Safety is our first priority™



Quality Management System and Product Type Approval:



Q1 0467



QMS 0726



Industrial Membership:



General Catalog No. 8-2023



Digital Chip embedded
with Certificate
for serial Traceability





8-501-02
8-501-04

8-501-08 and up

Digital Chip embedded
with Certificate
for serial Traceability

- Yoke Light Snatch Blocks are manufactured of the highest quality tensile steel.
- Available from 2 tonnes to 8 tonnes, for wire rope sizes 8mm to 19mm.
- Part number, wire rope size and working load limit are marked on each block.
- Permanent batch codes link to test certificates for easy traceability.
- Supplied with bronze bushings and 4.5”-14” with pressure lube fittings.
- Meets or exceeds all requirements of ASME B30.26.
- Safety factor 4:1
- Fatigue rated

Light Snatch Block with Shackle

Item No.	Sheave Dia.	Bearing Type	Wire Rope Size	Working Load Limit	N.W.	
	inch		mm	t*	lbs	kg
8-501-02	3	BB	8-10	2	4	2
8-501-04	4.5	BB	10-13	4	13	6
8-501-08	6	BB	16-19	8	29	13
8-501-0808	8	BB	16-19	8	44	20
8-501-0810	10	BB	16-19	8	46	21
8-501-0812-16	12	BB	16	8	49	22
8-501-0812-19	12	BB	19	8	49	22
8-501-0814-16	14	BB	16	8	56	25
8-501-0814-19	14	BB	19	8	56	25

*Minimum Ultimate Load is 4 times the Working Load Limit.



Digital Chip embedded
with Certificate
for serial Traceability

- YOKE Light Snatch Blocks are manufactured of the highest quality tensile steel.
- Available from 2 tonnes to 8 tonnes, for wire rope sizes 8mm to 19mm.
- Part number, wire rope size and working load limit are marked on each block.
- Permanent batch codes link to test certificates for easy traceability.
- Supplied with bronze bushings and 4.5"-14" with pressure lube fittings.
- Meets or exceeds all requirements of ASME B30.26.
- Safety factor 4:1
- Fatigue rated

Light Snatch Block with Hook

Item No.	Sheave Dia.	Bearing Type	Wire Rope Size	Working Load Limit	N.W.	
	inch		mm	t*	lbs	kg
8-502-02	3	BB	8-10	2	7	3
8-502-04	4.5	BB	10-13	4	13	6
8-502-08	6	BB	16-19	8	29	13
8-502-0808	8	BB	16-19	8	42	19
8-502-0810	10	BB	16-19	8	45	21
8-502-0812-16	12	BB	16	8	48	22
8-502-0812-19	12	BB	19	8	48	22
8-502-0814-16	14	BB	16	8	55	25
8-502-0814-19	14	BB	19	8	55	25

*Minimum Ultimate Load is 4 times the Working Load Limit.



Digital Chip embedded
with Certificate
for serial Traceability

- Yoke Forged Snatch Blocks are manufactured of the highest quality forged alloy steel.
- Available from 12 tonnes to 15 tonnes, for wire rope sizes 19mm to 22mm.
- Part number, wire rope size and working load limit are marked on each block.
- Permanent batch codes link to test certificates for easy traceability.
- Supplied with bronze bushings and pressure lube fittings.
- Meets or exceeds all requirements of ASME B30.26.
- Safety factor 4:1
- Fatigue rated

Forged Snatch Block with Shackle

Item No.	Sheave Dia.	Bearing Type	Wire Rope Size	Working Load Limit	N.W.	
	inch		mm	t*	lbs	kg
8-541-12	6	BB	19-22	12	52	24
8-541-15	8	BB	19-22	15	61	28
8-541-1510	10	BB	19-22	15	90	41

*Minimum Ultimate Load is 4 times the Working Load Limit.



Digital Chip embedded
with Certificate
for serial Traceability

- YOKE Forged Snatch Blocks are manufactured of the highest quality forged alloy steel.
- Available from 12 tonnes to 15 tonnes, for wire rope sizes 19mm to 22mm.
- Part number, wire rope size and working load limit are marked on each block.
- Permanent batch codes link to test certificates for easy traceability.
- Supplied with bronze bushings and pressure lube fittings.
- Meets or exceeds all requirements of ASME B30.26.
- Safety factor 4:1
- Fatigue rated

Forged Snatch Block with Hook

Item No.	Sheave Dia.	Bearing Type	Wire Rope Size	Working Load Limit	N.W.	
	inch		mm	t*	lbs	kg
8-542-12	6	BB	19-22	12	48	22
8-542-15	8	BB	19-22	15	64	29
8-542-1510	10	BB	19-22	15	92	42

*Minimum Ultimate Load is 4 times the Working Load Limit.



Digital Chip embedded with Certificate for serial Traceability

- Yoke Super Snatch Blocks are manufactured of the highest quality tensile steel.
- Available from 20 tonnes to 30 tonnes, for wire rope sizes 25mm to 32mm.
- Part number, wire rope size and working load limit are marked on each block.
- Permanent batch codes link to test certificates for easy traceability.
- Supplied with bronze bushings and pressure lube fittings.
- Meets or exceeds all requirements of ASME B30.26.
- Safety factor 4:1
- Fatigue rated

Super Snatch Block with Shackle

Item No.	Sheave Dia.	Bearing Type	Wire Rope Size	Working Load Limit	N.W.	
	inch		mm	t*	lbs	kg
8-551-20	8	BB	25-29	20	92	42
8-551-2010	10	BB	25-29	20	119	54
8-551-2012-25	12	BB	25	20	139	63
8-551-2012-29	12	BB	29	20	139	63
8-551-2014-29	14	BB	29	20	150	68
8-551-2518-25	18	BB	25	25	260	118
8-551-2518-29	18	BB	29	25	260	118

* Minimum Ultimate Load is 4 times the Working Load Limit.



Digital Chip embedded
with Certificate
for serial Traceability

- Yoke Super Snatch Blocks are manufactured of the highest quality tensile steel.
- Available from 20 tonnes to 30 tonnes, for wire rope sizes 25mm to 32mm.
- Part number, wire rope size and working load limit are marked on each block.
- Permanent batch codes link to test certificates for easy traceability.
- Supplied with bronze bushings and pressure lube fittings.
- Meets or exceeds all requirements of ASME B30.26.
- Safety factor 4:1
- Fatigue rated

Super Snatch Block with Hook

Item No.	Sheave Dia.	Bearing Type	Wire Rope Size	Working Load Limit	N.W.	
	inch		mm	t*	lbs	kg
8-552-20	8	BB	25-29	20	90	41
8-552-2010	10	BB	25-29	20	117	53
8-552-2012-25	12	BB	25	20	139	63
8-552-2012-29	12	BB	29	20	139	63
8-552-2015-29	14	BB	29	20	154	70
8-552-2518-25	18	BB	25	25	240	109
8-552-2518-29	18	BB	29	25	240	109
8-552-3020-29	20	BB	29	30	375	171
8-552-3020-32	20	BB	32	30	375	171
8-552-3024-29	24	BB	29	30	450	205
8-552-3024-32	24	BB	32	30	450	205

* Minimum Ultimate Load is 4 times the Working Load Limit.



Digital Chip embedded
with Certificate
for serial Traceability

- Yoke Alloy Snatch Blocks are manufactured of the highest quality alloy steel.
- Available in 12 tonnes, for wire rope sizes 19mm to 22mm.
- Part number, wire rope size and working load limit are marked on each block.
- Permanent batch codes link to test certificates for easy traceability.
- Supplied with bronze bushings and pressure lube fittings.
- Meets or exceeds all requirements of ASME B30.26.
- Safety factor 4:1
- Fatigue rated

Alloy Snatch Block with Shackle

Item No.	Sheave Dia.	Bearing Type	Wire Rope Size	Working Load Limit	N.W.	
	inch				lbs	kg
8-561-12	6	BB	19-22	12	28	13
8-561-1208	8	BB	19-22	12	37	17
8-561-1210	10	BB	19-22	12	46	21

*Minimum Ultimate Load is 4 times the Working Load Limit.



Digital Chip embedded
with Certificate
for serial Traceability

- YOKE Alloy Snatch Blocks are manufactured of the highest quality alloy steel.
- Available in 12 tonnes, for wire rope sizes 19mm to 22mm.
- Part number, wire rope size and working load limit are marked on each block.
- Permanent batch codes link to test certificates for easy traceability.
- Supplied with bronze bushings and pressure lube fittings.
- Meets or exceeds all requirements of ASME B30.26.
- Safety factor 4:1
- Fatigue rated

Alloy Snatch Block with Hook

Item No.	Sheave Dia.	Bearing Type	Wire Rope Size	Working Load Limit	N.W.	
	inch				lbs	kg
8-562-12	6	BB	19-22	12	31	14
8-562-1208	8	BB	19-22	12	37	17
8-562-1210	10	BB	19-22	12	46	21

*Minimum Ultimate Load is 4 times the Working Load Limit.



Digital Chip embedded
with Certificate
for serial Traceability

- YOKE Alloy HC Snatch Blocks are manufactured of the highest quality alloy steel.
- Available from 25 tonnes to 30 tonnes, for wire rope sizes 25mm to 32mm.
- Part number, wire rope size and working load limit are marked on each block.
- Permanent batch codes link to test certificates for easy traceability.
- Supplied with bronze bushings and pressure lube fittings.
- Meets or exceeds all requirements of ASME B30.26.
- Safety factor 4:1
- Fatigue rated

Alloy HC Snatch Block with Hook

Item No.	Sheave Dia.	Bearing Type	Wire Rope Size	Working Load Limit	N.W.	
	inch				lbs	kg
8-572-2508-25	8	BB	25	25	90	41
8-572-2508-29	8	BB	29	25	90	41
8-572-2510-25	10	BB	25	25	107	49
8-572-2510-29	10	BB	29	25	107	49
8-572-2510-32	10	BB	32	25	107	49
8-572-3012-25	12	BB	25	30	165	75
8-572-3012-29	12	BB	29	30	165	75
8-572-3014-25	14	BB	25	30	180	82
8-572-3014-29	14	BB	29	30	180	82

* Minimum Ultimate Load is 4 times the Working Load Limit.



Digital Chip embedded with Certificate for serial Traceability

- Yoke Oilfield Hoist Blocks are manufactured of the highest quality alloy steel.
- Available from 4 tonnes to 30 tonnes for wire rope sizes 8mm to 20mm.
- Part number, wire rope size and working load limit are marked on each block.
- Permanent batch codes link to test certificates for easy traceability.
- Supplied with sealed tapered bearings for extended product life and faster line speeds.
- Safety factor 4:1
- Manufactured by an API Q1 Certified facility.

Oilfield Hoist Block

Item No.	Sheave Dia.	Bearing Type	Wire Rope Size	Working Load Limit	N.W.	
	inch		mm	t*	lbs	kg
8-591-0408	8	TB	10-13	4	35	16
8-591-0810-13	10	TB	10-13	8	55	25
8-591-0810-15	10	TB	13-15	8	55	25
8-591-1214-16	14	TB	16	12	95	43
8-591-1214-19	14	TB	19	12	95	43

*Minimum Ultimate Load is 4 times the Working Load Limit.
TB=Tapered Bearing





- All parts are forged: swivel eye, side plates and sheave.
- Hot dipped galvanized finish provides corrosive resistance in salt water environment.
- Supplied with needle bearings and pressure lube fittings.
- Individually tested for maximum safety.

Trawl Block

with Swivel Eye

Item No.	Sheave Dimensions (inch)		Bearing Type	Working Load Limit	N.W.	
	inch	Rim Thickness		t*	lbs	kg
8-521-05	6	2 3/4	Needle bearing	5	27	12

★ Minimum Ultimate Load is 4 times the Working Load Limit.



- All parts are forged: swivel eye, side plates and sheave.
- Hot dipped galvanized finish provides corrosive resistance in salt water environment.
- Supplied with tapered bearings and pressure lube fittings.
- Individually tested for maximum safety.

Trawl Block

with Swivel Eye

Item No.	Sheave Dimensions (inch)		Bearing Type	Working Load Limit	N.W.	
	inch	Rim Thickness		t*	lbs	kg
8-523-10	8	2 7/8	Tapered bearing	10	44	20

★ Minimum Ultimate Load is 4 times the Working Load Limit.



- Forged swivel eye and sheave, pressed side plates with extra throat opening allowing nets and fittings to pass through.
- Hot dipped galvanized finish provides corrosive resistance in salt water environment.
- Supplied with bronze bushing and pressure lube fittings.
- Individually tested for maximum safety.

Trawl Block

with Swivel Eye

Item No.	Sheave Dimensions (inch)		Bearing Type	Working Load Limit	N.W.	
	inch	Rim Thickness		t*	lbs	kg
8-522-05	6	2 3/4	Bronze bushed	5	32	15

★ Minimum Ultimate Load is 4 times the Working Load Limit.