



EN STOCK

BOW SHACKLE


US TYPE SCREW PIN ANCHOR BOW SHACKLE G209 S209

(Hot ash zinc plating craft—More beautiful, more corrosion resistance; 6:1 SAFETY FACTOR)

Nominal Size (in.)	Working Load Limit (t)	Weight Each (lbs.)	Dimensions (in.)													Tolerance +/-	
			A	B	C	D	E	F	G	H	I	M	P	L	A	G	A
3/16	1/3	0.06	0.38	0.25	0.88	0.19	0.60	0.56	0.88	1.47	0.16	1.12	0.19	0.06	0.06		
1/4	1/2	0.10	0.47	0.31	1.13	0.25	0.78	0.61	1.28	1.84	0.19	1.38	0.26	0.06	0.06		
5/16	3/4	0.19	0.53	0.38	1.22	0.31	0.84	0.75	1.47	2.09	0.22	1.68	0.31	0.06	0.06		
3/8	1	0.31	0.66	0.44	1.44	0.38	1.03	0.91	1.78	2.49	0.26	2.05	0.38	0.13	0.06		
7/16	1-1/2	0.38	0.75	0.50	1.69	0.44	1.16	1.06	2.03	2.91	0.31	2.30	0.44	0.13	0.06		
1/2	2	0.72	0.81	0.63	1.88	0.50	1.31	1.19	2.31	3.28	0.38	2.69	0.50	0.13	0.06		
5/8	3-1/4	1.37	1.06	0.75	2.38	0.63	1.69	1.50	2.94	4.19	0.44	3.34	0.69	0.13	0.06		
3/4	4-3/4	2.35	1.25	0.88	2.81	0.75	2.00	1.81	3.50	4.97	0.50	3.97	0.81	0.25	0.06		
7/8	6-1/2	3.62	1.44	1.00	3.31	0.88	2.28	2.09	4.03	5.83	0.50	4.50	0.97	0.25	0.06		
1	8-1/2	5.03	1.69	1.13	3.75	1.00	2.69	2.38	4.89	6.66	0.56	5.07	1.06	0.25	0.06		
1-1/8	9-1/2	7.41	1.81	1.25	4.25	1.16	2.91	2.69	5.16	7.47	0.63	5.59	1.25	0.25	0.06		
1-1/4	12	9.92	2.02	1.38	4.69	1.29	3.25	3.00	5.75	8.25	0.69	6.16	1.38	0.25	0.06		
1-3/8	13-1/2	13.53	2.25	1.50	5.25	1.42	3.63	3.31	6.38	9.16	0.75	6.84	1.50	0.25	0.13		
1-1/2	17	17.20	2.36	1.63	5.75	1.54	3.88	3.63	6.88	10.00	0.81	7.35	1.62	0.25	0.13		
1-3/4	25	27.78	2.88	2.00	7.00	1.84	5.00	4.19	8.86	12.34	1.00	9.08	2.25	0.25	0.13		
2	35	45.00	3.25	2.25	7.75	2.08	5.75	4.81	9.97	13.68	1.22	10.34	2.40	0.25	0.13		
2-1/2	55	85.75	4.13	2.75	10.50	2.71	7.75	5.69	12.87	17.64	1.38	13.00	3.13	0.25	0.25		



Model :G209




US BOLT TYPE ANCHOR BOW SHACKLE G2130 S2130

(Hot ash zinc plating craft—More beautiful, more corrosion resistance; 6:1 SAFETY FACTOR)

Nominal Size (in.)	Working Load Limit (t)	Weight Each (lbs.)	Dimensions (in.)													Tolerance +/-	
			A	B	C	D	E	F	H	I	N	G	A			G	A
3/16	1/3	0.06	0.38	0.25	0.88	0.19	0.60	0.56	1.47	0.98	0.19	0.06	0.06				
1/4	1/2	0.11	0.47	0.31	1.13	0.25	0.78	0.61	1.84	1.28	0.25	0.06	0.06				
5/16	3/4	0.22	0.53	0.38	1.22	0.31	0.84	0.75	2.09	1.47	0.31	0.06	0.06				
3/8	1	0.33	0.66	0.44	1.44	0.38	1.03	0.91	2.49	1.78	0.38	0.13	0.06				
7/16	1-1/2	0.49	0.75	0.50	1.69	0.44	1.16	1.06	2.91	2.03	0.44	0.13	0.06				
1/2	2	0.79	0.81	0.63	1.88	0.50	1.31	1.19	3.28	2.31	0.50	0.13	0.06				
5/8	3-1/4	1.68	1.06	0.77	2.38	0.63	1.69	1.50	4.19	2.94	0.69	0.13	0.06				
3/4	4-3/4	2.72	1.25	0.88	2.81	0.75	2.00	1.81	4.97	3.50	0.81	0.25	0.06				
7/8	6-1/2	3.95	1.44	1.02	3.31	0.88	2.28	2.09	5.83	4.03	0.97	0.25	0.06				
1	8-1/2	5.66	1.69	1.15	3.75	1.00	2.69	2.38	6.66	4.69	1.06	0.25	0.06				
1-1/8	9-1/2	8.27	1.81	1.25	4.25	1.13	2.91	2.69	7.47	5.16	1.25	0.25	0.13				
1-1/4	12	11.71	2.02	1.40	4.69	1.29	3.25	3.00	8.25	5.75	1.38	0.25	0.13				
1-3/8	13-1/2	15.83	2.25	1.53	5.25	1.42	3.63	3.31	9.16	6.38	1.50	0.25	0.13				
1-1/2	17	20.80	2.36	1.66	5.75	1.53	3.88	3.63	10.00	6.88	1.62	0.25	0.13				
1-3/4	25	33.91	2.88	2.04	7.00	1.84	5.00	4.19	12.34	8.80	2.25	0.25	0.13				
2	35	52.25	3.25	2.30	7.75	2.08	5.75	4.81	13.68	10.15	2.40	0.25	0.13				
2-1/2	55	96.25	4.13	2.80	10.50	2.71	7.75	5.69	17.90	12.75	3.13	0.25	0.25				
3	85	154.00	5.00	3.30	13.00	3.12	7.88	6.50	21.50	14.62	3.62	0.25	0.25				
3-1/2	120	265.00	5.25	3.78	14.63	3.62	9.00	8.00	24.88	17.02	4.38	0.25	0.25				
4	150	338.00	5.60	4.26	14.50	4.00	10.00	9.00	25.68	18.00	4.56	0.25	0.25				



Model :G2130



D SHACKLE


US TYPE SCREW PIN ANCHOR D SHACKLE G210 S210

(Hot ash zinc plating craft—More beautiful, more corrosion resistance; 6:1 SAFETY FACTOR)

Nominal Size (in.)	Working Load Limit (t)	Weight Each (lbs.)	Dimensions (in.)													Tolerance +/-	
			A	B	C	D	E	F	G	K	L	M	G	A		G	A
1/4	1/2	0.11	0.47	0.31	0.25	0.25	0.97	0.62	0.97	1.59	0.19	1.43	0.06	0.06			
5/16	3/4	0.17	0.53	0.38	0.31	0.31	1.15	0.75	1.07	1.91	0.22	1.71	0.06	0.06			
3/8	1	0.26	0.66	0.44	0.38	0.38	1.42	0.92	1.28	2.31	0.25	2.02	0.13	0.06			
7/16	1-1/2	0.43	0.75	0.50	0.44	0.44	1.63	1.06	1.48	2.67	0.31	2.37	0.13	0.06			
1/2	2	0.99	0.81	0.63	0.50	0.50	1.81	1.18	1.66	3.03	0.38	2.89	0.13	0.06			
5/8	3-1/4	1.25	1.06	0.75	0.63	0.63	2.32	1.50	2.04	3.76	0.44	3.34	0.13	0.06			
3/4	4-3/4	2.63	1.25	0.88	0.81	0.75	2.75	1.81	2.40	4.53	0.50	3.97	0.25	0.06			
7/8	6-1/2	3.16	1.44	1.00	0.97	0.88	3.20	2.10	2.86	5.33	0.50	4.50	0.25	0.06			
1	8-1/2	4.75	1.69	1.13	1.00	1.00	3.69	2.38	3.24	5.94	0.56	5.13	0.25	0.06			
1-1/8	9-1/2	6.75	1.81	1.25	1.13	1.13	4.07	2.69	3.61	6.78	0.63	5.71	0.25	0.06			
1-1/4	12	9.06	2.03	1.38	1.38	1.25	4.53	3.00	3.97	7.50	0.69	6.25	0.25	0.13			
1-3/8	13-1/2	11.63	2.25	1.50	1.50	1.38	5.01	3.31	4.43	8.28	0.75	6.83	0.25	0.13			
1-1/2	17	15.95	2.38	1.63	1.62	1.50	5.38	3.62	4.84	9.05	0.81	7.33	0.25	0.13			
1-3/4	25	26.75	2.88	2.00	2.12	1.75	6.38	4.19	5.78	10.97	1.00	9.06	0.25	0.13			
2	35	42.31	3.25	2.25	2.30	2.10	7.25	5.00	6.77	12.74	1.13	10.35	0.25	0.25			
2-1/2	55	71.75	4.12	2.75	2.63	2.63	9.36	5.68	8.07	14.85	1.38	13.00	0.25	0.25			



Model :G210



US BOLT TYPE ANCHOR D SHACKLE G2150 S2150

(Hot ash zinc plating craft—More beautiful, more corrosion resistance; 6:1 SAFETY FACTOR)

Nominal Size (in.)	Working Load Limit (t)	Weight Each (lbs.)	Dimensions(in.)											Tolerance +/-	
			A	B	D	F	G	K	M	P	R	G	A		
1/4	1/2	0.13	0.47	0.31	0.25	0.62	0.91	1.59	0.97	1.56	0.25	0.06	0.06		
5/16	3/4	0.23	0.53	0.38	0.31	0.75	1.07	1.91	1.15	1.82	0.31	0.06	0.06		
3/8	1	0.33	0.66	0.44	0.38	0.92	1.28	2.31	1.42	2.17	0.38	0.13	0.06		
7/16	1-1/2	0.49	0.75	0.50	0.44	1.06	1.48	2.67	1.63	2.51	0.44	0.13	0.06		
1/2	2	0.75	0.81	0.64	0.50	1.18	1.66	3.03	1.81	2.80	0.50	0.13	0.06		
5/8	3-1/4	1.47	1.06	0.77	0.63	1.50	2.04	3.76	2.32	3.56	0.63	0.13	0.06		
3/4	4-3/4	2.52	1.25	0.89	0.75	1.81	2.40	4.53	2.75	4.15	0.81	0.25	0.06		
7/8	6-1/2	3.85	1.44	1.02	0.88	2.10	2.86	5.33	3.20	4.82	0.97	0.25	0.06		
1	8-1/2	5.55	1.69	1.15	1.00	2.38	3.24	5.94	3.69	5.39	1.00	0.25	0.06		
1-1/8	9-1/2	7.60	1.81	1.25	1.13	2.68	3.61	6.78	4.07	5.90	1.25	0.25	0.06		
1-1/4	12	10.81	2.03	1.40	1.25	3.00	3.97	7.50	4.53	6.89	1.38	0.25	0.06		
1-3/8	13-1/2	13.75	2.25	1.53	1.38	3.31	4.43	8.28	5.01	7.21	1.50	0.25	0.13		
1-1/2	17	18.50	2.38	1.66	1.50	3.62	4.87	9.05	5.38	7.73	1.62	0.25	0.13		
1-3/4	25	31.04	2.88	2.04	1.75	4.19	5.62	10.97	6.38	9.33	2.12	0.25	0.13		
2	35	46.75	3.25	2.30	2.10	5.00	6.82	12.74	7.25	10.41	2.36	0.25	0.13		
2-1/2	55	85.00	4.12	2.80	2.63	5.68	8.07	14.85	9.38	13.58	2.63	0.25	0.25		
3	85	124.25	5.00	3.25	3.00	6.50	8.56	16.87	11.00	15.33	3.00	0.25	0.25		